

Amendments to the Claims

This listing of the claims will replace all prior versions, and listings, of claims in the application.

Listing of the claims:

1. (Currently Amended) An apparatus for measuring ~~a constituent of a fluid~~ an attribute of ozone, the apparatus comprising:
 - a vessel to contain ~~an~~ the ozonated fluid;
 - a light source configured to direct a first band of light and a second band of light along a substantially shared path through the ozonated fluid in the vessel, wherein ~~the constituent ozone in the ozonated fluid~~ has a greater absorption associated with the first band of light than with the second band of light; and
 - a photosensor that senses the first band of light and the second band of light passing along the substantially shared path for measuring an attribute of the ozone in the ozonated fluid.
2. (Cancelled)
3. (Currently Amended) The apparatus of claim 2, wherein the vessel comprises a delivery pipeline for the ozonated fluid ~~water~~ to permit in situ measurement of the ozone.

4. (Original) The apparatus of claim 2, wherein the first band of light is associated with a yellow-red frequency and a first width, and the second band of light is associated with a blue frequency and a second width.
5. (Original) The apparatus of claim 4, wherein the light source comprises a yellow-red light-emitting diode to provide the first band of light, and a blue light-emitting diode to provide the second band of light.
6. (Original) The apparatus of claim 5, further comprising a second photosensor that senses the first band of light and the second band of light after they pass along at most a portion of the substantially shared path to detect differential aging of the light-emitting diodes.
7. (Currently Amended) The apparatus of claim 1, wherein the substantially shared path is defined in part by at least one reflection site to increase a length of the path through the ozonated fluid in the vessel, thereby increasing a measurement sensitivity for the ~~constituent~~ attribute of the ozone in the ozonated fluid.
8. (Original) The apparatus of claim 7, wherein the vessel comprises a material that defines an inner surface of the vessel that diffusely scatters the first and second bands of light at the at least one reflection site.
9. (Original) The apparatus of claim 7, further comprising a coating on an exterior surface of the vessel to provide diffuse scattering of the first and second bands of light at the at least one reflection site.

10. (Currently Amended) The apparatus of claim 1, wherein the ~~constituent~~ attribute of the ozone in the ozonated fluid has an absorption band that overlaps the first band of light.
11. (Original) The apparatus of claim 1, wherein the light source comprises a light-emitting diode.
12. (Original) The apparatus of claim 1, wherein the vessel comprises a material selected from the group of quartz and a polymer.
13. (Original) The apparatus of claim 1, wherein the photosensor senses the first band of light and the second band of light after the first band of light and the second band of light pass along the substantially shared path.
14. (Original) The apparatus of claim 1, wherein the photosensor senses the first band of light and the second band of light as the first band of light and the second band of light pass along the substantially shared path.
15. (Currently Amended) The apparatus of claim 1, further comprising at least one of a temperature sensor, for measuring a temperature of the ozonated fluid in the vessel, and a pressure sensor, for measuring a pressure of the ozonated fluid in the vessel.
16. (Currently Amended) An ozonated water generator, comprising:
 - a contactor for mixing water and ozone gas;
 - a pipeline in fluid communication with the contactor for delivery of ozonated water to a process tool;

a light source configured to direct a first band of light and a second band of light along a substantially shared path through the fluid in the pipeline, wherein ~~a constituent of~~ ozone in the ozonated water has a greater absorption associated with the first band of light than with the second band of light; and

a photosensor that senses the first band of light and the second band of light after they pass along the substantially shared path for measuring an attribute of the ozone in the ozonated fluid.

17. (Currently Amended) A method for measuring ~~a constituent~~ an attribute of ozone in an of a ozonated fluid, the method comprising:

selecting a first band of light for which ~~the constituent~~ ozone has a greater absorption than for a second band of light;

sensing the first band of light and the second band of light after they pass along a substantially shared path through the ozonated fluid; and

modifying a measured attribute of the ~~constituent~~ ozone in the ozonated fluid determined from the sensed first band of light in response to the sensed second band of light to improve the accuracy of the measured attribute.

18. (Currently Amended) The method of claim 17, wherein modifying comprises correcting the measured attribute for an intensity loss of the sensed first band of light associated with at least one factor other than absorption by the ~~constituent~~ attribute of the ozone in the ozonated fluid.

19. (Currently Amended) The method of claim 18, wherein the at least one factor comprises at least one of bubbles, a reflectivity of a reflection site of the substantially shared path, an impurity in the ozonated fluid, and a mechanical dimension of a vessel containing the ozonated fluid.
20. (Original) The method of claim 17, further comprising providing the substantially shared path in a vessel.
21. (Original) The method of claim 20, wherein the substantially shared path is defined in part by at least one reflection site to increase a length of the substantially shared path in the vessel.
22. (Currently Amended) The method of claim 20, ~~wherein the fluid is ozonated water, and~~ further comprising causing the ozonated water to flow through the vessel from an ozonated water generator to a process tool to permit in situ measurement of the ozone concentration.
23. (Original) The method of claim 17, further comprising alternately directing the first band of light and the second band of light along the substantially shared path, wherein sensing comprises alternately sensing the first band of light and the second band of light.
24. (Original) The method of claim 22, wherein alternately directing further comprises alternately directing no light along the substantially shared path.
25. (Original) The method of claim 22, wherein further comprising sensing at least one of the first band of light and the second band of light along at most a portion of the substantially

shared path, and responsively maintaining an emitted intensity of at least one of the first band of light and the second band of light.

26. (Original) A method for producing ozonated water having a desired ozone concentration, the method comprising:

selecting a first band of light for which the ozone has a greater absorption than for a second band of light;

generating ozonated water in a ozonated water generation device;

generating ozonated water in a ozonated water generation device;

sensing the first band of light and the second band of light after they pass along a

substantially shared path through the ozonated water after the ozonated water flows from the device;

modifying a measured ozone concentration determined from the sensed first band of light

in response to the sensed second band of light to improve the accuracy of the measured ozone concentration; and

adjusting at least one parameter of the device until the measured ozone concentration substantially matches the desired ozone concentration.

27. (New) The apparatus of claim 1 wherein the attribute is ozone concentration.

28. (New) The apparatus of claim 1 wherein the attribute is absorption of the first or second bands of light by the ozone.